

E PTM ASPHALT STABILISER

A unique high bonding formulation that when applied to the base course (Open Grade Friction Course) will penetrate into the material binding the structure into one solid mass. This greatly reduces moisture and saline environments affecting the integrity of the HMA (Hot Mix Asphalt) asphalt layer above.

This product can also be used for all asphalt surfaces where added strength is required to reduce the common problems for asphalt – moisture. Greatly reduces pot-holes, alligator lines, cracking, splits & de-bonding.

EPTM Asphalt Stabiliser is a non-hazardous, non-flammable, bio-degradable, non-carcinogenic and economical.

*Colour:	White - Milky
*Solubility in water:	Infinite
*Specific Gravity:	1.2
*Evaporation Rate:	slower than ether
*pH:	8.0
*Vapour Pressure:	N/A
*Vapour Density:	Heavier than air

Theoretical Coverage: 2 -3 square metres per one (1) litre

Method: Spray applied.

Consists of: 5 litre 20 litre 220 litre 1000 litre IBC (tote)

Shelf Life: 5 Years from date of manufacture when maintained in protected storage.





easy to use eco-friendly non toxic non flammable non Hazardous
COATINGS - CLEANERS - DEGREASERS - WATERPROOFING SYSTEMS
no mixing no special equipment non hazardous easy to use